


## **LIGHT BUT STRONG**







## SG casting gearbox with Forged crown-pinion:



## TIRTH AGRO TECHNOLOGY PRIVATE LIMITED

Regd.Office: "SHAKTIMAN", Unit-I, Survey No.-108/1, Plot No. B,NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat-INDIA, Pincode-360311

🖂 info@shaktimanagro.com @ www.shaktimanagro.com | CIN: U72900GJ2000PTC 038435 \* The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice. The Actual Machine can be different from the picture shown. \* Accessories shown are not part of standard equipment.



| Dhaanmitram                                 | SRT-9(270)/SS CD         | SRT-8(270)/SS CD |
|---|--------------------------|------------------|
| Overall Length (mm)                         | 1002                     | 1002             |
| Overall Width (mm)                          | 2680                     | 2460             |
| Extension Width (mm)                        | 3470                     | 3250             |
| Tilling Width (mm / inch)                   | 2620                     | 2400             |
| Overall Height (mm)                         | 1094                     | 1094             |
| Tractor Power (HP)                          | 40-60                    | 35-60            |
| (Kw)  | 30-44                    | 26-44            |
| 3-Point Hitch Type<br>No. of Tines (J-type) | CAT-II                   |                  |
| (Bracket type rotor) (Nos)                  | 70                       | 64               |
| PTO Input Speed (RPM)                       | 540                      |                  |
| Rotor Shaft Speed (RPM@540)                 | 281                      |                  |
| Standard Tine Construction                  | Curved                   |                  |
| Transmission Type                           | Chain                    |                  |
| Max. Working Depth (mm / inch)              | 170 / 6.7                |                  |
| Rotor Tube Diameter (mm / inch)             | 76 / 3.00                |                  |
| Rotor Swing Diameter (mm / inch)            | 406 / 16                 |                  |
| Drive line Safety Device                    | Slip Clutch / Shear Bolt |                  |
| Weight (Kg / lbs)                           | 370 / 750                | 320 / 705        |





