## **Fighter Rotary Tiller**





The Fighter series tillers are designed to be used uniquely for horticultural, agricultural, or commercial applications, to till soil for seedbed and planting preparation. They are designed to be mounted on tractors equipped with hydraulic lift and universal three point hitch that can support the implement weight, and driven by the power of the tractor through the PTO driveshaft.

## **Fighter Rotary Tiller**

MODEL	SRT 1.25	SRT 1.45	SRT 1.65	SRT 1.85
Overall Length (mm)	1390	1590	1745	1945
Overall Width (mm)	630			
Overall Height (mm)	1011.50			
Working Width (mm / inch)	1250 / 49	1450 / 57	1605 / 63	1805 /71
Recommended Tractor	-	-	30-40	35-50
Kw	-	-	23-30	26-37
3 Point Hitch Type	Cat I			
Frame Off-set (mm / inch)	102.5 / 4	102.5 / 4	102.5 / 4	102.5 / 4
No. of Tines (C-60x7)	36	42	48	54
No. of Tines (J-40x7)	-	_	60	72
PTO Input Speed (RPM)	540			
Rotor Shaft Speed (GD) (RPM@540)	215			
Rotor Shaft Speed (CD) (RPM@540)	238			
Standard Tine Construction	Curved / J-Type			
Transmission Type	Gear / Chain			
Max. Working Depth (mm / inch)	200 / 8			
Rotor Tube Diameter (mm / inch)	76 / 3 89 / 3.5			
Rotor Swing Diameter (mm / inch)	446 / 17.50			
Driveline Safety Device	Slip Clutch / Shear Bolt			
Weight (Gear Drive) (Kg / Lbs)	255 / 562	279 / 615	295 / 650	325 / 717
Weight (Chain Drive) (Kg / Lbs)	-	-	277 / 611	300 / 661



## **Tirth Agro Technology Private Limited**

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat- INDIA, Pincode-360311

+91 (02827) 234567, 270537 +91 (02827) 270457

info@shaktimanagro.com, www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435







<sup>\*</sup>The company reserves absolute rights to modify the specifications of machine and components there in without any prior notice.

<sup>\*</sup>Accessories shown are not part of standard equipment.