

SEMI CHAMPION ROTARY TILLER



Gear Drive

World's Largest Manufacturer of Rotary Tiller

SEMI CHAMPION ROTARY TILLER

MODEL	SRT - 4	SRT - 5	SRT - 5.5	SRT - 6	SRT - 7	SRT - 8	
Overall Length (mm)	1397	1743	1932	2009	2242	2464	
Overall Width (mm)	959						
Overall Height (mm)	1116						
Tilling Width (mm / inch)	1260 / 49.6	1606 / 63.2	1795 / 70.6	1872 / 73.7	2105 / 82.8	2327 / 91.6	
Tractor Power	HP	40-55	45-60	50-65	55-70	65-80	75-90
	Kw	30-41	34-45	37-48	41-52	49-60	56-67
3-Point Hitch Type	Cat - II						
Frame Off-set (mm / inch)	29/1.1	117 / 4.6	30/1.2	9/0.4	28/1.1	21/0.8	
No. of Tines (L/C-80x7)	30	36	36 & 42	42	48	54	
No. of Tines (L/C-70x7)	48	54	60	60	66	72	
No. of Tines (C/J-40x7)	48	60	66	72	84	90	
No. of Tines (Spike-Type)	34 & 46	37 & 48	54	46 & 58	70	78	
Standard Tine Construction	Curved / Square						
Transmission Type	Gear / Chain			Gear			
Max. Working Depth (mm / inch)	203 / 8						
Rotor Tube Diameter (mm / inch)	89 / 3.5						
Rotor Swing Diameter (mm / inch)	480 / 18.9						
Driveline Safety Device	Slip Clutch / Shear Bolt						
Weight (Kg / lbs)	432 / 954	464 / 1023	508 / 1120	514 / 1134	554 / 1223	592 / 1306	

The company reserves absolute rights to modify the specifications of machine and components therein without any prior notice.

"Weight is including safety guards & excluding PTO"

*Accessories shown are not part of standard equipment.



Tirth Agro Technology Pvt. Ltd.

"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza, Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat- INDIA, Pincode-360311

☎ +91 (02827) 234567, 270537 ☎ +91 (02827) 270457

✉ info@shaktimanagro.com, 🌐 www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435

Advantages

- Multipurpose Rotary Tiller suitable for both dryland & wetland cultivation.
- Suitable for medium to heavy soils.
- Helps in retaining moisture of the soil and improves aeration for better plant growth.
- Its specially designed ROTOR Blade reduces Load on Tractor, Diesel consumption and avoids tyre slippage.
- Suitable for 35 HP to 65 HP range tractors.
- Available with options of "L", "C", "J" and Spike type blades.
- Available in Chain / Multi Speed Gear Drive with Single / Multi Speed option.
- Available in 4 ft, 5 ft, 5.5 ft, 6 ft, 7 ft. and 8 ft width.

Rotor RPM Chart

Series	Input RPM	Gear Box	Spur Gear 1	Spur Gear 2	Rotor Speed
Semi (GD)	540	SS	-	-	218
		MS	16	19	184
			17	18	206
			18	17	231
		1000	MS	13	22

Standard Gear Pair 17-18

Scan to Visit Website



World's Largest Manufacturer of Rotary Tiller