

Fixed Offset Rotary Tiller



Features :-

- Offset Rotary Tiller
- Multi Speed Gear Box
- 3 Nos. Damper spring
- L type Blades
- Gear Driven Side Transmission in oil bath
- Durable attachment bracket
- Adjustable Skid Plate

Advantages :-

Suitable for inter cultivation in Orchard crop

Approaches Classed Magnes to be to detail the literal trade of the second the second of the second o

- Better weed removal and soil pulverization in horticulture crop
- Multipurpose rotary tiller suitable for both dryland & wetland cultivation.
- Save Fuel and Time
- Low Maintanance cost
- Increased Productivity

Fixed Offset Rotary Tiller



Technical Specifications

Description	UOM	SRT-6	
Overall Length	mm	2014	
Overall Width	mm	900	
Overall Height	mm	1120	
Tilling Width	mm	1780	
Tractor Power	HP	55-70	
Tractor Power	kW	4 7-60	
3-Point Hitch Type		CAT-II	
No. of blades (L-80x7)	Nos.	42	
Input shaft to si <mark>de drive distance</mark>	mm	603	
Input shaft to Stu <mark>b axle side distance</mark>	mm	1278	
PTO Input Speed	RPM	540	
Rotor Speed	RPM	As per Table	
Side Drive Type		Gear Drive	
Max. Working Depth	mm	140	
Damper Spring	Nos.	3	
Driveline Safety Device		Slip Clutch/ Shear Bolt	
Weight	kg/Lbs	484/1067	

Series	Rotor RPM	Spur Gear-1	Spur Gear-2	Rotor Speed
Semi (GD)	540	16	19	184
		19	16	259
		17	18	206
		18	17	231
	1000	12	24	186
		13	23	210
		14	22	236

^{*} The company reserves absolute rights to modify the specifications of machine and components there in without any prior notice.



Tirth Agro Technology Private Limited
"SHAKTIMAN", Survey No.-108/1, Plot No. B, NH-27, Nr. Bharudi Toll Plaza,
Bhunava (Village), Taluka: Gondal, Dist.: Rajkot. State: Gujarat- INDIA, Pincode-360311

3 +91 (02827) 234567, 270537 **□** +91 (02827) 270457 ☑ info@shaktimanagro.com, **⊕** www.shaktimanagro.com, CIN: U72900GJ2000PTC 038435

